

# AC Advertising Pedestal Series



## Innovativeness

One charger with two output sockets  
Business use with intelligent App control  
Vandal resistant and anti-corrosion



## Intelligent Control

Ethernet/4G/Wi-Fi communication all supported  
OCPP communication protocol with CMS  
Intelligent operation by App and cashless payment



## Large screen advertising revenue

55" HDV 2500cd/m<sup>2</sup>  
Remotely update AD content



## Product Parameter details

Model	YLEV14K-AD1	YLEV22K-AD2	YLEV44K-AD3
<b>Technical features</b>			
Charging capacity	Up to 14KW(7KW*2)	Up to 22KW(11KW*2)	Up to 44KW(22KW*2)
Input/Output power	230VAC±20%-50/60Hz-32A*2-1phase	400VAC±20%-50/60Hz-16A*2-3phase	400VAC±20%-50/60Hz-32A*2-3phase
RCD	RCMU(Type A+ DC 6mA)/ Type B RCCB(Optional)		
Standby power	<5W		
Measuring accuracy	1%		
Energy Meter	MID certified		
OCPP	OCPP1.6 Json(OCPP2.0 optional)		
Communication	WIFI/Ethernet/4G(Optional)		
User interface	LCD 5 inch Touch Screen/ RFID(mifare iso& IEC 14443A)		
Certificate/Compliance	CE/FCC/ROHS/REACH/IEC/EN 61851-1 , IEC/EN61851-21-2, IEC/EN 62955, EN300328, EN 301489-1/-17,EN62479.		
Charging Interface	Type 2 socket*2 or Type 2 Gun *2 5M		
Special Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
<b>Advertising display</b>			
LCD screen	55"IPS 1920*1080 16:9 HDV 2500cd/m <sup>2</sup>		
Application platform	Android 4.3 and above		
Communication	WIFI/Ethernet/4G(Optional)		
Ad update	USB flash disk,SD card, wired network remote release		
<b>Physical properties</b>			
Warranty	2 years		
Protection	IP55(outdoor)		
Special Protection	Topple & fall down protection		
Cooling	Natural cooling		
Operating temperature	-20C° to +55C°		
Humidity	Max.95%(non-regulating)		
Product Dimension	1950*920*290mm(L*W*H)		
Package Dimension	2110*450*1170mm(L*W*H)		
Net Weight	145kg		
GrossWeight.	201Kg		