

DC Advertising Pedestal Series



Innovativeness

One charger with two output sockets
Business use with intelligent App control
Vandal resistant and anti-corrosion



Intelligent Control

Ethernet/4G/Wi-Fi communication all supported
OCPP communication protocol with CMS
Intelligent operation by App and cashless payment



Large screen advertising revenue

55" HDV 2500cd/m²
Remotely update AD content



Product Parameter details

Model	YLEV60K-D4	YLEV120K-D5
Technical features		
Charging capacity	Up to 60KW	Up to 120KW
Input/Output power	400VAC±10%-50/60Hz- 3phase	
Power factor	≥0.98	
Efficiency	>95%	
Measuring accuracy	level 0.5	
Output voltage range	CCS: 250~1000VDC	
Output current range	0-180A	0-250A
Communication	PLC (between charger & vehicle)Ethernet/4G/OCPP 1.6J(optional)	
User interface	LCD 7 inch Touch Screen /RFID card and APP	
Versatility	EN/IEC 61851-1: 2019, EN/IEC 61851-23: 2014.	
Security design	Over/under voltage protection, overload protection, current leakage protection, grounding protection,lightening surge protection	
DC Plugs	CCS2 Cable 5M *2	
Energy Meter	CE certified or PTB (optional)	
RCD	Type A or Type B(optional)	
Advertising display		
Mainboard	Android based Quad-core	
RAM	2GB	
Storage	8GB, can extend to 32GB	
Video format	MPG,MPG-1,MPG-2,MPG-4,AVI,MP4, TS,MKV,WMV	
Maximum decoding resolution	3480x2160	
Picture format	GIF,JPEG,PNG,BMP	
Audio output	2x10W	
Audio format	MP3,24bit linear PCM7.1	
Other format	PDF/RSS, News/Weather-forecast	
Network	Rj45 interface,Wifi,4G,Option,	
The update way for content	Network remote update, U disk update.	
Display mode	Landscape/Portrait, Full Screen/Any Split Screen	
Program upgrade	Remote upgrade, remote upgrade	
Timer switch	Support any time period	
Panel parameters	Panel Type	55 inch LCD Panel
	Display area	1209*680mm
	Display ratio	16:9
	Backlight type	LED backlight
	Resolution	3480x2160
	Display color	16.7M
	Brightness	3500-cd/m ²
	Contrast	3500:1
	View angle	178°(H) / 178°(V)
	Response time	6ms
Life time	50000 hours	
Physical properties		
Warranty	3 years	
Protection	IP55(outdoor)	
Special Protection	Topple & fall down protection	
Cooling	Natural cooling	
Operating temperature	-30C° to +55C°	
Humidity	Max.95%(non-regulating)	
Dimensions	2310*1170*650(L*W*H)	
Net Weight	280Kg	
Gross Weight	321Kg	