

Voltplug -A61

A61W132EN18-DB / A61W332EN18-DB



Innovative

One charger with two output sockets Business use with intelligent App control Vandal resistant and anti-corrosion.

Secure and Safe

RCD Type A and 6mA DC residual current protection MID certified energy meter with accurate measurement

Intelligent

Ethernet/4G/WiFi communication all supported OCPP communication protocol with CMS Intelligent operation by App and cashless payment

Flexible

App operation /RFID authentication / Plug & Play Customization with different color painting



● Charging Style Display



Charger Parameter Details

Datasheet	Model	A61W332EN18-DB	A61W1332EN18-DB
Input	Power Supply	1P+N+PE	3P+N+PE
	Rated Voltage	230VAC	400VAC
	Rated Current	64A	64A
	Frequency	50/60Hz	50/60Hz
Output	Output Voltage	230VAC	400VAC
	Maximum Current	2x32A	2x32A
	Rated Power	2x7kW	2x22kW
User Interface	Charge Connector	Type 2 socket	Type 2 socket
	Enclosure	Galvanized steel	Galvanized steel
	left/Right Panel	Temper glass	Temper glass
	LED Indicator	Green/Yellow/Red 2.7"black &	Green/Yellow/Red
	LED Display	white screen	2.7"black & white screen
	RFID Reader	MifareISO/IEC14443 A	MifareISO/IEC14443 A
	Start Mode	Plug&Play/RFID card/App	Plug&Play/RFID card/App
	Emergency Stop	No	No
Communication	WiFi	Yes	Yes
	Ethernet	Yes	Yes
	3G/4G	Yes	Yes
	OCPP	OCPP1.6Json(OCPP 2.0 upgradable)	
Security and Safety	Energy Meter	MID certified	MID certified
	RCD	30mA Type A+6mA DC	30mA Type A+6mA DC
	Ingress Protection	IP54	IP54
	Impact Protection	IK08	IK08
	Electrical Protection	Over current protection, Residual current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over temperature protection	
	Certification	CE	CE
	Certification Standard	ENIEC 61851-1:2019, IEC 61851-1:2017, EC61851-21-2:2018	
	Warranty	2 Years	2 Years
Environment	Installation	Floor-stand	Floor-stand
	Work Temperature	-30°C~+50C	-30°C~+50C
	Work Humidity	5%~95%	5%~95%
	Work Altitude	<2000m	<2000m
Package	Product Dimension	1200*290*230mm(H*W*D)	1200*290*230mm(H*W*D)
	Package Dimension	1360*460*470mm(L*W*H)	1360*460*470mm(L*W*H)
	Net Weight	28.5kg	28.5kg
	Gross Weight	48.5kg	48.5kg
	External Package	Wood case	Wood case